

Create a new outdoor experience









CHARACTERISTICS

- 10mm tempered glass panels
- Perimatrical guide rail system
- Locking system
- Easy slide mechanism
- Door Handle
- Integrated drainage system

ADVANTAGES

Complete insulation Ideal for AC or heating Clear view, no aluminum frames Leaving the space open No hanging, no weight to the frame Many combinations Made to measure



Door Slide is a frameless sliding glass panel system, ideal to close and protect vertically openings of outdoor areas that require protection form any weather conditions.

The system is fixed inside the frame (aluminum, steel, concrete etc) with runners on all four sides. At the bottom runner there is also a specially design drainage system, making Door Slide completely waterproof.

There are two different models. The 3 way runner and the 5 way runner. Below are the different configurations provided. Dimensions are always made to measure

3 RUNERS MODEL




Single Side 2 Panels



Single Side 3 Panels



Double Side 8 Panels



Double Side 10 Panels


5 RUNERS MODEL




Single Side 4 Panels



Single Side 4 Panels



Double Side 8 Panels



Double Side 10 Panels



Integrated drainage system










CHARACTERISTICS

- 10mm tempered glass panels
- Top guide rail system
- Locking system
- Easy slide mechanism
- Door Handle


ADVANTAGES

Ideal for AC or heating Clear view, no aluminum frames Leaving the space open Many combinations Made to measure




The system is fixed inside the frame (aluminum, steel, concrete etc) with ran aluminum top runner. At the bottom the system is completely free, allowing easy passage. There are two different models. The folding and the bi-folding with hinges. Below are the different models. Dimensions are always made to measure

FOLDING MODEL



BI-FOLDING MODEL





Door Fold models are operating with a hanging mechanism and always require steel or concrete supporting frame.



High Low is a retractable glass system designed to protect shaded areas from wind, cold and heat. The operation is manual with counterweights, or with electric motor. There is always one fixed panel at the bottom and another one or two are retracting downwards with no effort at all. HighLow is available in two models: FREESTANDING / TELESCOPIC **BUILT-IN MANUAL / ELECTRIC** Dimensions are always made to measure.









TELESCOPIC Without pillars and 6mm laminate top glass and 8mm tempered bottom glass. The retractable panel has always a thin aluminum frame.

BUILT-IN MANUAL / ELECTRIC MODEL



With or without motor, in 2 or th3 panels and 10mm tempered glass panels. The panels are frameless and the counterweights are integrated inside the vertical guide rails.



CHARACTERISTICS

FREESTANDING

- Ideal to protect open areas or areas shaded with parasols and awnings
- Create an ellegant glass fence
- Protect from strong wind
- Adjustable at any height
- Made to measure

BUILT-IN

- Total closure, perfect to use them in AC areas
- Easy slide mechanism for smooth retraction
- Framelss panels that do not interrupt the view from inside
- Adjustable at any height
- Made to measure

Electric models are operated by Somfy motors

HEAD OFFICES Konstantinoupoleos 61 136 75 Athens Greece T: +30 6944573797 F: +30 210 2389996 **GCC** BRANCH DWC Dubai Free Zone Dubai - UAE T: +971 52 1378228 W: www.shadingoutdoors.com in fo@shading outdoor.com

